

AD-A066 372


NAVAL POSTGRADUATE SCHOOL MONTEREY CALIF  
DESIGN AND PERFORMANCE OF A FREQUENCY HOPPING COMMUNICATIONS SY--ETC(U)  
DEC 78 H KUCUKOGLU

F/G 17/4

UNCLASSIFIED

NL

| OF |  
AD  
A066372



END  
DATE  
FILMED  
'5--79'  
DDC

AD A0 66372

DDC FILE COPY,

LEVEL II

23.5

# NAVAL POSTGRADUATE SCHOOL

Monterey, California



## THESIS

DESIGN AND PERFORMANCE OF A  
FREQUENCY HOPPING COMMUNICATIONS SYSTEM  
USING DELTA MODULATION

by

Habib Kucukoglu

December 1978

Thesis Advisor:

G. Myers

Approved for public release; distribution unlimited.

79 03 26 066

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Design and Performance of a Frequency Hopping Communications System Using Delta Modulation.		5. TYPE OF REPORT & PERIOD COVERED Master's Thesis <del>December 1978</del>
7. AUTHOR(s) Habib Kucukoglu		6. PERFORMING ORG. REPORT NUMBER
8. PERFORMING ORGANIZATION NAME AND ADDRESS Naval Postgraduate School Monterey, California 93940		9. CONTRACT OR GRANT NUMBER(s)
11. CONTROLLING OFFICE NAME AND ADDRESS Naval Postgraduate School Monterey, California		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) 53 p.		12. REPORT DATE December 1978
		13. NUMBER OF PAGES 52
		15. SECURITY CLASS. (of this report) Unclassified
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report)  Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Frequency Hopping Communications System Spread Spectrum		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number)  A way to increase jamming immunity and to decrease the intercept probability of a communication system is to use spread spectrum (SS) techniques. In this report a frequency hopping SS system (transmitter and receiver) is presented. This system is designed, built, and tested to send and receive digitized voice by utilizing a single chip delta modulator/demodulator.		

DD FORM 1473  
1 JAN 73  
(Page 1)EDITION OF 1 NOV 68 IS OBSOLETE  
S/N 0102-014-6601

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

254<sup>1</sup> 450

xlt



UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

(20. ABSTRACT CONT'D)

The report describes the circuitry employed, lists the important parameters of the system and includes photographs of various waveforms. The recovered audio is of good quality using digital data rates as low as 25 kilobits per second. A hopping rate of 100 hops per second is used in the design.

ACCOMPLISHED FOR	
NTIS	<input checked="" type="checkbox"/> Yes Section
DDC	<input type="checkbox"/> B.H. Section
UNANNOUNCED	
JUSTIFICATION	
BY	DISTRIBUTION/AVAILABILITY CODES
DATE	1/1/73 or SPECIAL
A	

DD Form 1473  
Jan 73  
S/N 0102-014-6601

UNCLASSIFIED



Approved for public release; distribution unlimited.

Design and Performance of a  
Frequency Hopping Communications System  
Using Delta Modulation

by

Habib Kucukoglu  
Lieutenant, Turkish Navy  
B.S.E.E., Naval Postgraduate School, 1977

Submitted in partial fulfillment of the  
requirements for the degree of

MASTER OF SCIENCE IN ELECTRICAL ENGINEERING

from the

NAVAL POSTGRADUATE SCHOOL  
December 1978

Author

*H. Kucukoglu*


Approved by:

*Allen Myers* Thesis Advisor

*Rudolf Panholzer* Second Reader

*De Kik*  
Chairman, Department of Electrical Engineering

*William M. Tolles*  
Dean of Science and Engineering




## ABSTRACT

A way to increase jamming immunity and to decrease the intercept probability of a communication system is to use spread spectrum (SS) techniques.

In this report a frequency hopping SS system (transmitter and receiver) is presented. This system is designed, built, and tested to send and receive digitized voice by utilizing a single chip delta modulator/demodulator.

The report describes the circuitry employed, lists the important parameters of the system and includes photographs of various waveforms. The recovered audio is of good quality using digital data rates as low as 25 kilobits per second. A hopping rate of 100 hops per second is used in the design.



## TABLE OF CONTENTS

I.	INTRODUCTION -----	7
II.	BACKGROUND -----	8
	A. FREQUENCY HOPPING -----	8
	B. DELTA MODULATION -----	11
III.	THE EXPERIMENTAL SYSTEM -----	17
	A. PSEUDO-RANDOM SEQUENCE GENERATOR --	19
	B. DIGITAL TO ANALOG CONVERTER (DAC) -	23
	C. MODULATION NETWORK -----	25
	D. VOLTAGE CONTROLLED OSCILLATOR -----	25
	E. MIXER -----	27
	F. IF AMPLIFIER -----	28
	G. LIMITER, DEMODULATOR, DATA AMPLIFIER -----	28
	H. PULSE COUNTING DEMODULATOR (PCD) --	29
	I. AUDIO AMPLIFIER -----	33
IV.	CONCLUSIONS AND RECOMMENDATIONS -----	34
	A. CONCLUSIONS -----	34
	B. RECOMMENDATIONS -----	35
	APPENDIX -----	36
	LIST OF REFERENCES -----	51
	INITIAL DISTRIBUTION LIST -----	52



#### ACKNOWLEDGEMENT

The author wishes to thank Professor Glen A. Myers of the Electrical Engineering Department, Naval Postgraduate School of Monterey, California, for his valuable advice and guidance.

## I. INTRODUCTION

This study considers the performance of a frequency hopping (FH) voice communications system. With FH, the carrier frequency of the radiated signal is caused to vary in a discrete manner (hop) over some predetermined range. The hop rate is a variable in the design.

In a typical FH system, the analog voice signal is converted to a digital signal. The digits (bits in binary conversion) are then transmitted. The receiver converts the digital signal back to analog form. Pulse code modulation is a common form of analog-to-digital conversion (ADC). In this work, a new integrated circuit (IC) delta modulator was chosen for the ADC.

This report presents the design, characteristics, and test results of a particular frequency hopping system that uses delta modulation for ADC. The quality of the recovered signal is excellent for data rates as low as 25 kilobits per second. A hopping rate of 100 hops per second is used in this system.

## II. BACKGROUND

### A. FREQUENCY HOPPING

Frequency hopping (FH) is one possible type of spread spectrum system. FH can be defined as data transmission using many frequency channels in a predetermined sequence as shown in Fig. 1.




FIG. 1. FREQUENCY-TIME DIAGRAM OF A FH SYSTEM

In the figure shown above  $B$  is the total available bandwidth whereas  $b$  corresponds to the system bandwidth per hop. The dwell time in a particular frequency channel is given as  $t_d$ . Binary data can be sent by using frequency offset as shown in Fig. 1.



It can be readily shown that FH systems provide some immunity to jamming. A detailed discussion of FH system performance is given in Ref. 1. A simplified block diagram of a frequency hopping transmission system is given in Fig. 2.

For FH systems, high speed, digitally programmed frequency synthesizers are usually used. The pseudo random (PR) sequence generator of Fig. 2 provides a long repeating sequence of bits. The value of the output frequency of the synthesizer is selected by subgroups of this pseudo random sequence. Thus, the output frequency of the synthesizer "hops" to a new value whenever a different command comes from the binary pseudo random code generator. Then, the data modulates the hopped signal.

A simplified block diagram of a FH receiver is shown in Fig. 3. The receiver system contains a synchronized PR code generator and a frequency synthesizer which serves as a synchronous local oscillator. The IF amplifier has a bandwidth greater than  $b$  Hertz. A transmitted signal having frequencies:  $f_1, f_2, \dots, f_n$  is converted to a constant IF by means of the synchronous local oscillator in the receiver. Therefore, the bandwidth of the IF stage of a FH receiver is determined by the data bandwidth and the carrier modulation technique used.




FIG. 2. FREQUENCY HOPPING (FH) TRANSMITTER




FIG. 3. A FH RECEIVING SYSTEM


## B. DELTA MODULATION

Delta modulation is one technique used to convert an analog message into a digital waveform. A basic difference between pulse code modulation (PCM) and delta modulation is that PCM represents the magnitude of the analog voltage while delta modulation represents the slope of the analog voltage as shown in Fig. 4. The block diagram of a basic delta modulator is given in Fig. 5.


The delta modulation technique of Fig. 5 is improved by using variable slope delta (VSD) and continuously variable slope delta (CVSD) modulation algorithms. The practical results obtained by using these algorithms are improved fidelity and wider dynamic range. The block diagram of a CVSD modulator is shown in Fig. 6.

For this project, a single chip CVSD modulator/demodulator is used to digitize the message. The bit rate is the same as the clock frequency. Using a 25 kHz clock rate gave a good performance for a voice signal bandlimited to the range 300 Hz to 3 kHz. The oscilloscope traces in Fig. 7 show the CVSD outputs for a sinusoidal input at different frequencies and different sampling rates.






a) Analog Voltage



b) Output of Delta Modulator



c) Discrete From of  $v(t) = \int d(t) dt$

FIG. 4. BASIC DELTA MODULATION WAVEFORMS




FIG. 5. BASIC DELTA MODULATION






FIG. 6. CVSD MODULATOR BLOCK DIAGRAM



a)  $f_{\text{sig}} = 1.2 \text{ kHz}$

b) Delta Modulator  
output at  
25 kbit/sec



a)  $f_{\text{sig}} = 100 \text{ Hz}$

b) Delta Modulator  
output at  
10 kbit/sec

FIG. 7. CVSD MODULATOR



The delta demodulator is basically an integrator. However, the CVSD demodulator contains additional circuitry similar to that in the modulator. A block diagram of the CVSD demodulator is shown in Fig. 8.






FIG. 8. CVSD DEMODULATOR BLOCK DIAGRAM

The oscilloscope traces of the sinusoidal inputs to the modulator and the reconstructed sinusoidal waveforms at the output of the CVSD demodulator are shown in Fig. 9.



a) Original analog  
signal  
( $f = 1.1$  kHz)

b) CVSD demodulator  
output before  
low-pass filtering



a) Original analog  
signal  
( $f = 1.1$  kHz)

b) CVSD demodulator  
output (after  
low-pass  
filtering)

FIG. 9. CVSD DEMODULATOR

### III. THE EXPERIMENTAL SYSTEM

The block diagram of the experimental frequency hopping transmitting-receiving system is shown in Fig. 10. For this application, voice is used as the message. The analog signal,  $v(t)$ , is digitized by a delta modulator. The two-level (bipolar) voltage frequency modulates a carrier whose frequency is caused to hop in a pseudo random manner.

The receiver de-hops the transmitted signal with a synchronously hopping local oscillator. Thus, the receiver IF remains constant. In this work, no attempt was made to isolate the receiver and transmitter. Receiver synchronization was provided by hardwire from the transmitter section. A frequency demodulator extracts the digitized message. This signal is converted to the analog equivalent,  $v(t)$  by a delta demodulator. The audio is filtered and amplified by the final stages and applied to a speaker.

A single clock with frequency dividing circuitry provides the adequate hopping rate and analog data sampling rate for delta modulation/demodulation. The building blocks of the system are described in the following sections.






FIG. 10. BLOCK DIAGRAM OF THE FREQUENCY HOPPING TRANSMITTER-RECEIVER

### A. PSEUDO-RANDOM SEQUENCE GENERATOR

A pseudo-random (PR) sequence code generator is an essential part of many spread spectrum (SS) systems. In a frequency hopping system, these codes can be used to determine the hopping pattern of the RF signal. These codes are generated with maximal length code generators (feedback shift registers).

For this project, six stages of an 8 bit shift register (74164) and an EX-OR gate (7486), which is modified as an EX-NOR gate, are used for generating a  $2^6 - 1 = 63$  bit length code by making the feedback connections shown in Fig. 11. The shift register states and their corresponding decimal values are listed in Table 1. The output voltage (sequence) of the code generator is shown in Fig. 12.





FIG. 11. PSEUDO RANDOM CODE GENERATION

Clock Pulse	Decimal Number	Clock Pulse	Decimal Number	Clock Pulse	Decimal Number	Clock Pulse	Decimal Number	Clock Pulse	Decimal Number	Clock Pulse	Decimal Number	Clock Pulse	Decimal Number	Clock Pulse	Decimal Number
1	0	9	127	17	63	25	95	33	15	41	119	49	51	57	85
2	128	10	191	18	159	26	175	34	135	42	187	50	153	58	42
3	192	11	223	19	207	27	215	35	195	43	221	51	76	59	21
4	224	12	239	20	231	28	235	36	225	44	110	52	166	60	10
5	240	13	247	21	243	29	245	37	112	45	55	53	83	61	5
6	248	14	251	22	249	30	122	38	184	46	155	54	169	62	2
7	252	15	253	23	124	31	61	39	220	47	205	55	84	63	1
8	254	16	126	24	190	32	30	40	238	48	102	56	170	64	0

TABLE 1. DECIMAL EQUIVALENT OF THE PR SEQUENCE



a) Clock input  
b) PR code sequence

FIG. 12. PR CODE GENERATION



A frequency divider and reset circuit are part of the code generator as shown in Fig.13 . The frequency divider determines the hopping rate. It is capable of dividing the clock frequency by 1, 2, 4 ... 256 by suitable programming. The schematic diagram of the frequency divider is given in Appendix.

For EX-NOR operation, all "ones" in the shift register will cause the sequence to stop. This does not occur theoretically since the contents of the shift register is all "zeros" when the voltage is applied to the system. However, transients and different delay times may cause the contents to be all "ones" at some time. A way to prevent the all ones state from persisting is to use an 8 - Input NAND gate which generates a "0" whenever all ones appear. This "0" clears the contents of the shift register and starts the sequence again.




FIG. 13. PR CODE GENERATOR WITH PROTECTION CIRCUIT

## B. DIGITAL TO ANALOG CONVERTER (DAC)

To use the code generator output for frequency hopping, the decimal equivalents of the binary codes must be obtained. Discrete voltage levels, which are used to "hop" the frequency of an oscillator, are generated from the PR sequence (or codes) by means of a DAC.

For this application, an 8-bit, high speed DAC (DAC-08 BC) followed by an op-amp (u741) worked well. The decimal values listed in Table 1 are converted to voltage levels such that decimal "0" gives 0 volt output and decimal "255" gives 10V. The output stage of the DAC can be given for any state as follows

$$V_o(nT) = \frac{10}{255} D$$

where

D is the decimal value in that state

T is the duration of that state

$$0 \leq n \leq 63$$


For example, the output voltage of the DAC at state 30 is (from Table 1),

$$V_o = \frac{10}{255} \cdot 122 = 4.78 \text{ Volts}$$

These voltage levels are shown in Fig. 14.

In Fig. 14b, the level transition times are a few microseconds (because of the op-amp used). This limits the rate of frequency hopping. In this application the data rates of 25 KBits/sec and hopping rates of 100 hops/sec were easily compatible with the microsecond transition times.






a) 63 bit period  
of DAC output  
voltage

b) Clock  
 $f = 25 \text{ kHz}$

FIG. 14a. PR SEQUENCE



a) Discrete voltage  
levels of DAC  
output

b) Clock  
 $f = 25 \text{ kHz}$

FIG. 14b. PR VOLTAGE LEVELS

### C. MODULATION NETWORK

The message  $v(t)$  is converted to a digital waveform  $d(t)$  by using delta modulation, and  $d(t)$  then modulates a carrier. For this application, FM (or frequency shift keying, FSK, for digital FM transmission) is used.

The modulation network combines the hopping voltage and modulation voltage. Thus, the output of the modulation network is

$$V_m \text{ out} = k_1 V_{\text{hop}} + k_2 d(t)$$

where the constants  $k_1$  and  $k_2$  are chosen to give the desired performance. The block diagram of the modulation network is given in Fig. 15. The data modulator provides the data modulation without interfering with the receiver VCO.

The output voltage waveform of the data modulator is shown on the oscilloscope trace of Fig. 16.

### D. VOLTAGE CONTROLLED OSCILLATOR

An essential part of a frequency hopping system is the voltage controlled oscillator. Some of the key parameters of a VCO are: frequency stability, frequency range, linearity, and response time.

For this application, two VCOs are used. One for the transmitter and one as a receiver local oscillator. Both are built from TTL NOR gates connected to form a multivibrator. The schematic diagram is shown in the Appendix.





FIG. 15. MODULATION NETWORK BLOCK DIAGRAM



a) Data input

b) Output of data  
modulation  
network

FIG. 16. MODULATION NETWORK OUTPUT



When the output of the DAC is applied to the input of a VCO, the frequency of the RF signal "hops" to a new value. The frequency of a VCO can be formulated as

$$f(V_c) = f_o + \frac{V_c}{V_{c \text{ max}}} \Delta f$$

where

$V_c$  = control voltage of VCO

$\Delta f$  = Maximum frequency change

For this project

$V_{c \text{ max}} = 5.0V$  and  $\Delta f = 656 \text{ kHz}$

$f_o = 1024 \text{ kHz}$  for transmitter VCO

$f_o = 1690 \text{ kHz}$  for receiver VCO.

The frequency versus voltage curves of the VCOs are shown in Fig. 17.

Linearity of the VCO is very good in the ranges shown in Fig. 17. For FSK modulation this property is not very important since only two different frequencies are used. However, in FH the number of channels used are large. These frequency channels must be equispaced depending on the RF modulation technique used.

#### E. MIXER

The receiving system utilizes a double balanced mixer (RELCOM-MI) which provides 50 dB rejection of the RF and local oscillator signals at the output.




FIG. 17. VOLTAGE-FREQUENCY CHARACTERISTICS OF VCOs

#### F. IF AMPLIFIER

With the mixer used, a conventional one-stage IF amplifier delivers adequate band selectivity and power gain for the data demodulation process. The IF amplifier circuit diagram with mixer stage is given in Appendix A-5. A high gain transistor (2N3404) is employed with input and output IF transformers. This amplifier has the following characteristics:

$$A_v = 1.2$$

$$f_c = 645 \text{ kHz}$$

$$Bw (3dB) = 68 \text{ kHz}$$

The voltage gain,  $A_v$  is measured at the secondary winding of the output IF transformer which is used for the low impedance interface of the next stage (amplifier/limiter transistor). The low impedance output with modest voltage gain provides considerable power gain. The bandwidth of this stage is adjusted to accommodate the FSK signal at a rate of 25 kilobits/sec. The result is also useful at 50 kilobits/sec (due to the limiting process of the following stage).

#### G. LIMITER, DEMODULATOR, DATA AMPLIFIER

The demodulator is a pulse counting discriminator. The relatively low center frequency (645 kHz) of the IF amplifier, the wide pass band (70 kHz) of the IF amplifier, the digital nature of the demodulated waveform, and the simplicity of the design and operation make this type of demodulator more attractive than others (ratio detectors or phase-locked loops).



#### H. PULSE COUNTING DEMODULATOR (PCD)

The block diagram of a PCD is shown in Fig. 17.




FIG. 18. PULSE COUNTING DISCRIMINATOR

The operation of PCD is illustrated in Fig. 19. When an unmodulated RF signal is applied to the system, the limiting action shapes the waveform as shown in Fig. 19a. The limiter output is rectified by a half wave rectifier and applied to the monostable multivibrator (one shot). It generates pulses  $V_a(t)$  of constant duration =  $\tau$  sec. The average of these pulses has a constant DC value  $V_o(t)$ . However, any FM signal has a non-constant time  $T$  for one cycle of the carrier. The inverse of  $T$  is proportional to the message amplitude. These variations cause the DC level of the output  $V_o(t)$  to change at the same rate as the modulating signal waveform. In this manner, a replica of the message is obtained as  $V_o(t)$ .

For this application, the output of the monostable multivibrator (74121) is averaged by a two-stage RC low-pass filter. The demodulated data waveform is amplified in the first stage of the amplifier. Before the next stage, another low-pass filter is used to decrease the high frequency content of the final amplifier-limiter output. The output is TTL compatible.






FIG. 19. PCD OPERATION



a) IF input

b) Limiter output



a) One-shot output

b) IF signal

FIG. 20. PCD



The schematic diagram of the PCD is given in Appendix A-8 .  
Limiter action and pulse generation are shown in Fig. 20.


#### I. AUDIO AMPLIFIER

The output of the CVSD demodulator reconstructs the analog message,  $v(t)$ . However, a one stage low pass filter employed for this purpose is not adequate. The level of the high frequency components shown in Fig. 9a must be reduced. For this reason a four-pole active Butterworth lowpass filter is used to recover the original message,  $v(t)$ . Its cut-off frequency is chosen as 3.1 kHz. The result is shown in Fig. 9b. To provide audio power level required to drive a speaker, an IC audio amplifier (LM 380) is used.

## CONCLUSIONS AND RECOMMENDATIONS

### A. CONCLUSIONS

A frequency hopping system is one choice available for military communication systems. Jamming resistance is the major advantage in the military allocated RF spectrum. The system designed and built as part of this project worked well. The results of overall data modulation-demodulation process including frequency hopping and dehopping are shown on the oscilloscope traces in Fig. 21.



a) Delta  
Modulator  
Output

b) Demodulated  
Signal  
(Input to the  
delta  
demodulator)

FIG. 21. FREQUENCY HOPPING SYSTEM PERFORMANCE

## B. RECOMMENDATIONS

To improve the jamming immunity of FH systems, the number of frequency channels possible should be large. A higher frequency VCO with better stability could also give improved results. Alternatively, a high speed frequency synthesizer with two outputs (one for the transmitter section and the other for the receiver L.O. injection) can completely eliminate the mismatching problem between the transmitter and receiver.

For digitization of the voice signal, delta modulation seems to give good results with relatively low bit rates. The delta modulator-demodulator chip used for this worked well. Employing an additional low-pass filter section at the analog input of the delta modulator and providing additional low pass filtering at the output of the delta demodulator will give a higher signal-to-noise ratio for the voice signal.

A phase-locked loop can be employed as a carrier demodulator, if the center frequency of the IF amplifier is increased by using higher frequencies for transmission.



## APPENDIX

This appendix contains the schematic diagrams of all the circuits used in this work. The components used to implement the various systems include TTL gates (EX-OR, NAND, NOR gates), astable and monostable multivibrators, shift registers, counters, DAC, operational amplifiers, IC audio amplifier, and a single chip delta modulator/demodulator. Operating characteristics of each component are found in reference .

The various circuit diagrams are presented in Figures A-1 through A-9 in the following order:

Fig A-1: Clock and Frequency Divider

Fig A-2: PR Code Generator with Protection Circuit

Fig A-3: DAC

Fig A-4: Carrier Modulator-Hopping Circuit

Fig A-5: VCO

Fig A-6: Delta Modulator/Demodulator

Fig A-7: Mixer - IF Amplifier

Fig A-8: Limiter - PCD Amplifier

Fig A-9: LP Filter - Audio Amplifier

The values of all capacitors are in micro ( $10^{-6}$ ) farads unless otherwise indicated.

Fig A-1 shows the clock and the divide by 255 counter.

The clock frequency was set at 25 kHz by choosing the resistor and capacitor values indicated. The output of the clock is directly applied to the delta modulator and demodulator to first digitize the message and then reconstruct the message from the digitized form respectively. The clock output is also applied to the frequency divider. The output frequency ( $\frac{25,000}{255} \approx 100$  Hz) if the divider is applied to the PR code generator.

In Fig A-2, an 8-Bit shift register (74164) with EX-OR gates, one of which is used as an inverter, generates the 63 bit PR sequence by means of serial feedback. This shift register is a serial in, parallel out type. This allows the outputs to be applied to the DAC. An 8-Input NAND gate is also driven from these terminals. Whenever all the contents (outputs) of the shift register are "1", the NAND gate generates a "0" which clears the shift register contents, thus starting the PR sequence again.

Fig A-3 is the schematic of the DAC. The decimal equivalent of the digital input is first converted into a current value. Then, this current (2 mA for decimal 255) is applied to an external op-amp which converts this current to a voltage (10 volts for decimal 255). The scale adjustment is made by a potentiometer and zener diode.

The carrier modulator - hopping circuit shown in Fig A-4 has two op-amps ( $\mu$  741) and potentiometers. The first op-amp isolates the data modulation input from the local oscillator VCO hopping circuit. The final op-amp is used as a differential

amplifier which gives an output,  $V_o = \frac{R_2}{R_1} (V_1 - V_2)$  where  $V_1$  is the data output and  $V_2$  is the hopping voltage. The output of the final op-amp is applied to the transmitter VCO. One of the potentiometers is used to match the local oscillator VCO of the receiver and the other one is used to set the frequency deviation of FSK for carrier modulation.

The VCO design in Fig A-5 uses a single package TTL quad 2-Input NOR gates (7402), two switching diodes, resistors, timing capacitors and a buffer stage. The capacitors  $C_1$  and  $C_2$  determine the operating frequency whereas  $R_1$  and  $R_2$  are used to adjust the frequency range of the VCO. The buffer stage contains a low power, high speed switching transistor (2N2222) with a coupling and biasing network. This stage is necessary for output waveform shaping, and it eliminates the frequency drift due to load variations. For this application the carrier frequency is hopped in a predetermined PR sequence between the frequencies of 1024 kHz and 1397 kHz.

The same schematic is used as a local oscillator in the receiver. For this purpose,  $C_1$  and  $C_2$  are changed to give new frequencies of 1690 kHz and 2063 kHz.

This provides the same hopping range of  $1397 - 1024 = 373$  kHz and  $2063 - 1690 = 373$  kHz, which provides a constant IF defined as

$$\begin{aligned} f_{LO} - f_c &= 1690 - 1024 = 666 \text{ kHz} \\ &= 2063 - 1397 = 666 \text{ kHz} \end{aligned}$$

in the absence of data modulation.

Using the same type of VCO in the transmitter and receiver



helps the system have similar transient responses during the hopping intervals, decreases the possible mismatching of transmitter-receiver system, and simplifies the design.

Fig A-6 shows the schematic diagram of the delta modulator/demodulator. It is a single chip (MC 3418) continuously variable slope delta (CVSD) modulator/demodulator. The same chip can be used both as modulator or demodulator by connecting pin 15 to the resistor shown or to  $V_{cc}$  respectively. For this application, two chips are used: one as a modulator in the transmitter, and the other as a demodulator in the receiver. The resistor and capacitor values determine the clock rate of the system. Using the values shown in Fig A-6, voice input (300-3000 Hz) is digitized by a 25 kHz clock to give a 25 kilobit/sec output bit rate.

The mixer - IF amplifier section is shown in Fig A-7. The double balanced mixer (RELCOM-MI) provides a 50 dB carrier rejection. In this application the carrier frequency  $f_c = 1024$  kHz and the intermediate frequency  $f_{IF} = 645$  kHz are relatively close. Thus, carrier suppression at the output of the mixer is essential.

The IF amplifier has a relatively wide bandwidth ( $\approx 70$  kHz). This is obtained by connecting a resistor (15 k $\Omega$ ) in parallel with the output IF transformer. With perfect matching between the transmitter instantaneous frequency and the receiver local oscillator instantaneous frequency during the frequency hopping, the instantaneous IF varies between 620 kHz and 670 kHz.

This variation is caused by the two-level data. With a center frequency of 645 kHz, the IF amplifier bandwidth thus includes the main lobe of the signal spectrum. This bandwidth is obtained by adjusting the IF transformers. Finally, a single stage conventional IF amplifier provides the desired selectivity and voltage gain.

Fig A-8 shows the carrier demodulator schematic diagram. The input is the IF amplifier output. This IF signal is amplified and converted to a unipolar rectangular waveform by the discrete transistor limiter circuit. The voltage levels of this waveform are TTL compatible. Thus, the limiter output is directly connected to the monostable multivibrator (74121) input. The monostable multivibrator is adjusted to generate constant duration pulses (0.9 micro second) with the resistor and capacitor values shown. The averaging circuit consists of a second order RC lowpass filter. The values of the resistors and capacitors are chosen in such a way that the demodulated signal has negligibly small rise and fall times while the high frequency components (due to the pulse output of the monostable multivibrator) are filtered. The operation of this type of demodulator is discussed in the previous sections.

The demodulated signal is then amplified. A one-pole RC low-pass filter is used before the final stage of amplification. The final amplifier stage is used to interface the data,  $d(t)$  with the delta demodulator.


In Fig A-9, a fourth-order Butterworth active low-pass filter is shown with the audio amplifier circuitry. The capacitor

and resistor values given determine the bandwidth of 3.1 kHz with a slope of 24 dB/octave. This filter produces the replica of the original message  $v(t)$  at the delta demodulator output.

The audio amplifier is an IC type (LM 380). It provides the power (a few watts) needed to drive an 8 ohm speaker.










FIG. A - 3 DAC






FIG. A - 4. CARRIER MODULATOR / HOPPING CIRCUIT




FIG. A- 5 VOLTAGE CONTROLLED OSCILLATOR









FIG. A - 2 MIXER - IF AMPLIFIER



$Q_1, Q_2, Q_3 = 2N\ 2222$

FIG. A - 8 . LIMITER - PCD - AMPLIFIER




FIG. A-9 LP FILTER - AUDIO AMPLIFIER



#### LIST OF REFERENCES

1. Dixon, R.C., Spread Spectrum Systems, p. 26-27, John Wiley & Sons, 1976.
2. Spilker, James J., Digital Communications by Satellite, p. 110-111, Prentice Hall, 1977.
3. Lancaster, Don, TTL Cookbook, p. 244, p. 278-280, Howard W. Sams & Co., 1974.
4. Motorola Semiconductor Information and Application Notes (XC 3417, XC 3418), September 1977.

# INITIAL DISTRIBUTION LIST

	No. Copies
1. Defense Documentation Center Cameron Station Alexandria, Virginia 22314	2
2. Library, Code 0142 Naval Postgraduate School Monterey, California 93940	2
3. Department Chairman, Code 52 Department of Electrical Engineering Naval Postgraduate School Monterey, California 93940	2
4. Assoc. Prof. G. Myers, Code 52Mv Department of Electrical Engineering Naval Postgraduate School Monterey, California 93940	2
5. Assoc. Prof. R. Panholzer, Code 52Pz Department of Electrical Engineering Naval Postgraduate School Monterey, California 93940	1
6. Deniz Kuvvetleri Komutanlığı Eğitim Dairesi ANKARA - TURKEY	2
7. Istanbul Teknik Üniversitesi Elektrik Fakültesi Gümüşsuyu ISTANBUL-TURKEY	1
8. Boğaziçi Üniversitesi P.K. 2 Bebek, ISTANBUL - TURKEY	1
9. Orta Doğu Teknik Üniversitesi ANKARA - TURKEY	1
10. Mr. Steve Kelly Motorola Semiconductor Products, Inc. 4020 Moorpark Avenue, Suite 116 San Jose, California 95117	1
11. Habib Küçüköğlu Fevzipaşa Cad. No. 235 Karagömrük, ISTANBUL - TURKEY	2